

DATA SHEET: PROTECT42

- Protective film -

FOIL

Film Type
 Film Thickness (μm)
 Film Weight (gsm)
 Gloss (60°)
 Elongation (%)
 Dimensional Stability (FTM 14)
 Adhesive Type
 Adhesive Thickness (μm)
 Peel Strength on Stainless Steel 24 hrs
 (N/25mm)
 Adhesive Color

Polyvinyl coating
 25 (+/- 10%)
 36
 65
 MD > 120
 MD < 0.40 mm
 Solvent Acrylic
 20-25
 9.6
 Clear

LINER

Liner Weight (gsm)
 Liner Type
 Liner Thickness (μm)

73
 White PE-Coated One Sided Kraft
 75

PERFORMANCE GUIDANCE

Application Temperature
 Service Temperature
 Shelf Life
 Storage Temp / Rel. Humidity
 Outdoor Durability
 Indoor application

> +50 °F
 -40 °F to 221 °F
 2 years
 71 °F / 50%
 10 years
 up to 12 years

Folagility GmbH

Geschäftsführer: René Arndt | Kai Tolksdorf
 Heinz-Kerneck-Str. 8 | 28307 Bremen

Handelsregister: HRB 41654 HB
 USt.-IdNr.: DE 455 691 232
 Steuernummer: 60/112/05087

Bank: Landesbank Baden-Württemberg
 IBAN: DE08 6005 0101 0001 3675 15
 BIC: SOLADEST600

Tel: +49 421 33 70 85 51
 Mail: info@folagility.com
 Web: www.folagility.com