

MasterJet S Dot Fix Basic

Highlights

- Bubble-free & easy to apply
- residue-free removable spot adhesive



	Technical
Material	Monomeric soft PVC film
Colour	White and transparent, both matt and glossy
Area	For short to medium-term indoor use such as temporary advertising spaces at POS or in shopping malls, short-term trade fair and event signage, shop window decorations and promotional stickers. For easy, bubble-free application. Not suitable for non-polar surfaces.
Covering material	Single-sided coated silicone paper, 120 g/sqm, white
Adhesive	Polyacrylate, removable, transparent, repositionable
Adhesive strength (AFERA 4001, 24 hours)	>1.5 N/25 mm
Thickness (without protective paper and adhesive)	100 µm ±10
Bonding temperature	+18 °C to +25 °C
Operating temperature	-30 °C to +50 °C
Printing process	<p>Inkjet printing with solvent-based inks, UV or latex inks. The liner used may cause flatness restrictions with individual printing systems. We recommend conducting your own tests.</p> <p>When printing with UV printers with intense UV radiation, premature ageing (embrittlement) of the transparent films may occur. We recommend conducting your own tests.</p>
Fire behaviour	Testing in accordance with EN 13501 is in preparation.
Storage conditions (in original packaging, at 18-25 °C and 40-65 % relative humidity)	12 months
Processing instructions	<p>The print should be completely dry before the material is further processed or laminated. For solvent printing, a drying time of at least 24 hours is recommended. The material should be stored loosely rolled up to allow air to circulate. The surface to be covered should be clean, dry and free of dust, grease or silicone residues – this will ensure optimum adhesion of the film. Wet application is not recommended. The films can usually be removed easily and without residue from most substrates. However, adhesive residues may remain on PVC surfaces. On surfaces that become very hot (e.g. shop windows, metal), it is advisable to allow the material to cool before removing it to facilitate clean removal. Adhesive residues (if any) can be removed with methylated spirits. We recommend storing the product upright in its original box.</p>

MasterJet S Dot Fix Basic

Characterisation according to REACH	The product is a product in accordance with Regulation (EC) No. 1907/2006 Article 3 (REACH Regulation).
SVHC / REACH	Based on the supplier declarations available to us, we can confirm that this product does not contain any of the substances in a concentration of more than 0.1% by weight that are included in the list of Substances of Very High Concern (SVHC) for authorisation issued by the European Chemicals Agency (ECHA) (https://echa.europa.eu/de/candidate-list-table).
Dimensions	SFI-MDFB* - Dimensions on request

This information corresponds to the current state of our knowledge and is intended to provide non-binding information about the products and their possible applications. No legally binding assurance of certain properties can be derived from our information. All information is provided without guarantee. Status 06|2025